



Technical Specifications

Part	Kerf	OD (Outer Diameter)	Z (# of Teeth)	RD (Rim Depth)	RT (Rim Thickness)	Ø Hub	HT (Hub Thickness)	Ø Bore
IF-180-024-25-0.85	0.049	1.25	z24	25	0.85	130	2.90	50/60/65
IF-180-024-25-1.10	0.063	1.60	z24	25	1.10	130	2.90	50/60/65
IF-180-024-40-0.90	0.053	1.35	z24	40	0.90	100	2.90	50/60
IF-180-024-40-1.15	0.065	1.65	z24	40	1.15	100	2.90	50/60
IF-180-024-47-0.95	0.053	1.35	z24	47	0.95	86	2.90	50
IF-180-024-40-1.10	0.065	1.65	z24	47	1.10	86	2.90	50
IF-200-028-25-0.85	0.049	1.25	z28	25	0.85	150	2.90	50/60/65
IF-200-028-25-1.10	0.063	1.60	z28	25	1.10	150	2.90	50/60/65
IF-200-028-40-0.90	0.053	1.35	z28	40	0.90	120	2.90	50/60/65
IF-200-028-40-1.15	0.065	1.65	z28	40	1.15	120	2.90	50/60/65
IF-200-028-50-0.95	0.053	1.35	z28	50	0.95	100	2.90	50/60/65
IF-200-028-50-1.10	0.065	1.65	z28	50	1.10	100	2.90	50/60/65
IF-220-028-25-0.85	0.049	1.25	z28	25	0.85	170	2.90	50/60/65
IF-220-028-25-1.10	0.063	1.60	z28	25	1.10	170	2.90	50/60/65
IF-220-028-40-0.90	0.053	1.35	z28	40	0.90	140	2.90	50/60/65
IF-220-028-40-1.15	0.065	1.65	z28	40	1.15	140	2.90	50/60/65
IF-220-028-50-0.95	0.053	1.35	z36	50	0.95	120	2.90	50/60/65
IF-220-028-50-1.10	0.065	1.65	z36	50	1.10	120	2.90	50/60/65
IF-235-030-25-0.85	0.049	1.25	z30	25	0.85	185	2.90	50/60/65
IF-235-030-25-1.10	0.063	1.60	z30	25	1.10	185	2.90	50/60/65
IF-235-030-40-0.90	0.053	1.35	z30	40	0.90	155	2.90	50/60/65
IF-235-030-40-1.15	0.065	1.65	z30	40	1.15	155	2.90	50/60/65
IF-235-030-50-0.95	0.053	1.35	z36	50	0.95	135	2.90	50/60/65
IF-235-030-50-1.10	0.065	1.65	z36	50	1.10	135	2.90	50/60/65
IF-255-036-25-0.85	0.049	1.25	z36	25	0.85	205	2.90	50/60/65
IF-255-036-25-1.10	0.063	1.60	z36	25	1.10	205	2.90	50/60/65
IF-255-036-40-0.90	0.053	1.35	z36	40	0.90	175	2.90	50/60/65
IF-255-036-40-1.15	0.065	1.65	z36	40	1.15	175	2.90	50/60/65
IF-255-036-50-0.95	0.053	1.35	z36	50	0.95	155	2.90	50/60/65
IF-255-036-50-1.10	0.065	1.65	z36	50	1.10	155	2.90	50/60/65
IF-255-036-60-1.00	0.059	1.50	z36	60	1.00	135	2.90	50/60/65
IF-255-036-60-1.15	0.069	1.75	z36	60	1.15	135	2.90	50/60/65
IF-255-036-70-1.10	0.063	1.60	z36	70	1.10	115	2.90	50/60/65
IF-255-036-70-1.30	0.075	1.90	z36	70	1.30	115	2.90	50/60/65
IF-270-036-50-0.95	0.053	1.35	z36	50	0.95	170	2.90	50/60/65
IF-270-036-50-1.10	0.065	1.65	z36	50	1.10	170	2.90	50/60/65
IF-270-036-60-1.00	0.059	1.50	z36	60	1.00	150	2.90	50/60/65
IF-270-036-60-1.15	0.069	1.75	z36	60	1.15	150	2.90	50/60/65
IF-270-036-70-1.10	0.063	1.60	z36	70	1.10	130	2.90	50/60/65
IF-270-036-70-1.30	0.075	1.90	z36	70	1.30	130	2.90	50/60/65
IF-270-036-70-1.50	0.083	2.10	z36	70	1.50	130	2.90	50/60/65
IF-270-036-80-1.20	0.067	1.70	z36	80	1.20	110	2.90	50/60/65
IF-270-036-80-1.40	0.079	2.00	z36	80	1.40	110	2.90	50/60/65
IF-270-036-80-1.60	0.087	2.20	z36	80	1.60	110	2.90	50/60/65

Integral Flange Splitting Saws are designed with a robust body that provides maximum beam strength and stiffness. This allows the blade to withstand higher cutting forces and faster feed rates. The result is longer and more reliable run times between sharpening with more accuracy.

To help us quote the right blade for you, please [contact](#) one of our knowledgeable sales staff and let us know about your application and what goals you are looking to achieve.

Bore Pattern Specs

Machine MFG	Bore	Pinhole	Keyway Specs
ETP Hydro-Grip	65mm	(3) 10.5mm Pinholes on 80mm BC	N/A
ETP Hydro-Grip	60mm	(3) 10.5mm Pinholes on 74mm BC	N/A
ETP Hydro-Grip	50mm	(3) 10.5mm Pinholes on 64mm BC	N/A