



## Technical Specifications

Part	Kerf		OD (Outer Diameter)	Z (# of Teeth)	PT (Plate Thickness)	Flange Diameter
SP-220-028-1.20	0.063	1.60	220mm	z28	1.20mm	120mm
SP-220-028-1.20	0.071	1.80	220mm	z28	1.20mm	120mm
SP-220-028-1.40	0.079	2.00	220mm	z28	1.40mm	120mm
SP-220-028-1.60	0.087	2.20	220mm	z28	1.60mm	120mm
SP-220-028-1.80	0.094	2.40	220mm	z28	1.80mm	120mm
SP-200-028-1.10	0.059	1.50	200mm	z28	1.10mm	120mm
SP-200-028-1.20	0.063	1.60	200mm	z28	1.20mm	120mm
SP-200-028-1.20	0.079	2.00	200mm	z28	1.20mm	120mm
SP-200-028-1.40	0.087	2.20	200mm	z28	1.40mm	120mm
SP-200-028-1.60	0.094	2.40	200mm	z28	1.60mm	93mm
SP-220-028-1.10	0.059	1.50	220mm	z28	1.10mm	120mm
SP-220-028-1.20	0.063	1.60	220mm	z28	1.20mm	120mm
SP-220-028-1.20	0.079	2.00	220mm	z28	1.20mm	120mm
SP-220-028-1.40	0.087	2.20	220mm	z28	1.40mm	120mm
SP-220-028-1.60	0.094	2.40	220mm	z28	1.60mm	120mm

**Our Straight Plate Splitting Saws** are built to the tightest tolerances, raising the bar above industry standards for accuracy and performance. Available in both several varieties, and with a kerf specific to your application.

**To help us quote the right blade for you**, please [contact](#) one of our knowledgeable sales staff and let us know about your application and what goals you are looking to achieve.

## Bore Pattern Specs

Sleeve MFG	Bore	Pinhole	Keyway Specs
ETP Hydro-Grip	65mm	(3) 10.5mm Pinholes on 80mm BC	N/A
ETP Hydro-Grip	60mm	(3) 10.5mm Pinholes on 74mm BC	N/A
ETP Hydro-Grip	50mm	(3) 10.5mm Pinholes on 64mm BC	N/A