



### Technical Specifications

Part	Kerf		OD (Outer Diameter)	Z (# of Teeth)	RD (Rim Depth)	RT (Rim Thickness)	Timber Thickness
IF-305-036-40-1.40	2.30mm	.091"	12"	z36	40mm	1.40mm	5/4" Max
IF-305-036-40-1.80	2.70mm	.106"	12"	z36	40mm	1.80mm	5/4" Max
IF-305-036-40-2.10	3.10mm	.122"	12"	z36	40mm	2.10mm	5/4" Max
IF-305-036-55-1.60	2.60mm	.102"	12"	z36	55mm	1.60mm	8/4" Max
IF-305-036-55-2.00	3.00mm	.118"	12"	z36	55mm	2.00mm	8/4" Max
IF-305-048-40-1.40	2.30mm	.091"	12"	z48	40mm	1.40mm	5/4" Max
IF-305-048-40-1.80	2.70mm	.106"	12"	z48	40mm	1.80mm	5/4" Max
IF-305-048-40-2.10	3.10mm	.122"	12"	z48	40mm	2.10mm	5/4" Max
IF-305-048-55-1.60	2.60mm	.102"	12"	z48	55mm	1.60mm	8/4" Max
IF-305-048-55-2.00	3.00mm	.118"	12"	z48	55mm	2.00mm	8/4" Max
IF-305-056-40-1.40	2.30mm	.091"	12"	z56	40mm	1.40mm	5/4" Max
IF-305-056-40-1.80	2.70mm	.106"	12"	z56	40mm	1.80mm	5/4" Max
IF-305-056-40-2.10	3.10mm	.122"	12"	z56	40mm	2.10mm	5/4" Max

**Integral Flange Rip Saws** are designed with a robust body that provides maximum beam strength and stiffness. This allows the blade to withstand higher cutting forces and faster feed rates. The result is longer and more reliable run times between sharpening with more accurate glue-line cuts.

To help us quote the right blade for you, please [contact](#) one of our knowledgeable sales staff and let us know about your application and what goals you are looking to achieve.

### Bore Pattern Specs

Machine MFG	Ø Bore	Ø Pinhole	Keyway Specs
CML	95.00mm	N/A	DKW W: 20.00mm x L: 6.00mm
CML	75.00mm	(8) 5.5mm on 86mm BC	DKW W: 24.00mm x L: 6.00mm

[sales@superthinsaws.com](mailto:sales@superthinsaws.com)