



Technical Specifications

Part	Kerf	OD (Outer Diameter)	Z (# of Teeth)	PT (Plate Thickness)	Flange Diameter	Max Timber Width
SP-220-028-1.20	0.063"	1.60mm	z28	1.20mm	120mm	90mm
SP-220-028-1.20	0.079"	2.00mm	z28	1.20mm	120mm	90mm
SP-220-028-1.40	0.087"	2.20mm	z28	1.40mm	120mm	90mm
SP-220-028-1.60	0.094"	2.40mm	z28	1.60mm	120mm	90mm
SP-220-028-1.80	0.102"	2.60mm	z28	1.80mm	120mm	90mm
SP-225-028-1.20	0.063"	1.60mm	z28	1.20mm	120mm	95mm
SP-225-028-1.20	0.079"	2.00mm	z28	1.20mm	120mm	95mm
SP-225-028-1.40	0.087"	2.20mm	z28	1.40mm	120mm	95mm
SP-225-028-1.60	0.094"	2.40mm	z28	1.60mm	120mm	95mm
SP-225-028-1.80	0.102"	2.60mm	z28	1.80mm	120mm	95mm
SP-230-030-1.20	0.063"	1.60mm	z30	1.20mm	120mm	100mm
SP-230-030-1.20	0.079"	2.00mm	z30	1.20mm	120mm	100mm
SP-230-030-1.40	0.087"	2.20mm	z30	1.40mm	120mm	100mm
SP-230-030-1.60	0.094"	2.40mm	z30	1.60mm	120mm	100mm
SP-230-030-1.80	0.102"	2.60mm	z30	1.80mm	120mm	100mm
SP-255-036-1.20	0.071"	1.80mm	z36	1.20mm	120mm	125mm
SP-255-036-1.40	0.079"	2.00mm	z36	1.40mm	120mm	125mm
SP-255-036-1.60	0.094"	2.40mm	z36	1.60mm	120mm	125mm
SP-255-036-1.80	0.102"	2.60mm	z36	1.80mm	120mm	125mm

Our Straight Plate Splitting Saws are built to the tightest tolerances, raising the bar above industry standards for accuracy and performance. Available in both several varieties, and with a kerf specific to your application.

To help us quote the right blade for you, please [contact](#) one of our knowledgeable sales staff and let us know about your application and what goals you are looking to achieve.

Bore Pattern Specs

Sleeve MFG	Bore	Pinhole	Keyway Specs
ETP Hydro-Grip	65mm	(3) 10.5mm Pinholes on 80mm BC	N/A
ETP Hydro-Grip	60mm	(3) 10.5mm Pinholes on 74mm BC	N/A
ETP Hydro-Grip	50mm	(3) 10.5mm Pinholes on 64mm BC	N/A