



### Technical Specifications

Part	Kerf		OD (Outer Diameter)	Z (# of Teeth)	PT (Plate Thickness)	Timber Thickness
SP-305-036-2.20	3.20mm	.126"	12"	±36	2.20mm	5/4" Max
SP-305-036-2.50	3.50mm	.138"	12"	±36	2.50mm	5/4" Max
SP-305-036-2.80	3.90mm	.154"	12"	±36	2.80mm	5/4" Max
SP-305-048-2.20	3.20mm	.126"	12"	±48	2.20mm	5/4" Max
SP-305-048-2.50	3.50mm	.138"	12"	±48	2.50mm	5/4" Max
SP-305-048-2.80	3.90mm	.154"	12"	±48	2.80mm	5/4" Max

**Our Straight Plate Rip Saws** are built to the tightest tolerances, raising the bar above industry standards for accuracy and performance. Available in both Glue-Line and Rip-to-Dimension varieties, and with a kerf specific to your application.

**To help us quote the right blade for you**, please [contact](#) one of our knowledgeable sales staff and let us know about your application and what goals you are looking to achieve.

### Bore Pattern Specs

Machine MFG	Ø Bore	Ø Pinhole	Keyway Specs
Progressive	3.125"	N/A	DKW W: 13.2mm x L: 4.19mm
Progressive	3.750"	N/A	DKW W: 12.7mm x L: 4.19mm

[sales@superthinsaws.com](mailto:sales@superthinsaws.com)